

Please enter the following amended claims:

7. (Amended) A rotor of a dynamo-electric machine, said rotor comprising:

*C1
cont.*
a rotor coil comprising a bobbin having a first flange and a second flange opposed to each other, and a conductor wound around said bobbin, wherein current flows through said conductor to generate magnetic flux;

a field core assembly covering said rotor coil, said field core assembly comprising a first field core member and a second field core member respectively having triangular magnetic poles alternately meshed with each other; and

a plurality of discrete magnetic portions provided between adjacent ones of said triangular magnetic poles in an orientation that reduces the leakage of magnetic flux between said triangular magnetic poles, and wherein said plurality of magnetic portions abut at least one of said first flange and said second flange in order to join said plurality of magnetic portions to said bobbin, wherein said plurality of magnetic portions are formed with a resin mixed with ferrite-based iron filings.

*C1
cancel*

8. (Amended) A rotor of a dynamo-electric machine, said rotor comprising:
a rotor coil comprising a bobbin having a first flange and a second flange opposed to each other, and a conductor wound around said bobbin, wherein current flows through said conductor to generate magnetic flux;

a field core assembly covering said rotor coil, said field core assembly comprising a first field core member and a second field core member respectively having triangular magnetic poles alternately meshed with each other; and

a plurality of discrete magnetic portions provided between adjacent ones of said triangular magnetic poles in an orientation that reduces the leakage of magnetic flux between said triangular magnetic poles, and wherein said plurality of magnetic portions abut at least one of said first flange and said second flange in order to join said plurality of magnetic portions to said bobbin,

wherein said plurality of magnetic portions comprise magnetic members made of a magnetic material, and covers covering said magnetic members, and wherein said covers and said bobbin are made of a same non-magnetic resin material.

Please enter the following new claims 17-19 as follows:

*C2
cont.*

17. (New) A rotor of a dynamo-electric machine as claimed in Claim 8, wherein fitting portions are formed on sides of said magnetic portions to prevent said magnetic portions from shifting radially outward, said fitting portions fitting against sides of said triangular magnetic poles.

18. (New) A rotor of a dynamo-electric machine as claimed in Claim 8, wherein engaging portions are formed on ends of said magnetic portions and engage with ends of said triangular magnetic poles to prevent said magnetic portions from shifting axially.

AMENDMENT UNDER 37 C.F.R. § 1.116
US Appln. 09/817,252

Atty. Docket: Q63136

*C2
cancel* 19. (New) A rotor of a dynamo-electric machine as claimed in Claim 8, wherein said plurality of magnetic portions and said bobbin are formed as a unitary structure by injection molding.
